

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1863522.990 Y=78996.780				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-49				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER G Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-7-02 12-7-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -25.1 Ft.			
9. TOTAL DEPTH OF HOLE 19.5 Ft.				18. TOTAL CORE RECOVERY FOR BORING 98 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-25.1	.0		Light tannish gray fine quartz sand, abundant gray, tan, and white shell fragments in fine to coarse gravel range, scattered large whole shells in medium to coarse gravel range. 10 YR 8/1 (SP)	100		-25.1	0
-29.9	4.8		Light gray fine quartz sand, scattered white to gray shell fragments in fine gravel range. 10 YR 8/0.5-8.5/0.5 (SP)	100		-30.1	5
						Large gray shell fragment at 6.5 ft.	
-35.5	10.4		Light tannish gray fine quartz sand, scattered shell fragments in fine gravel range, trace of silt. 10 YR 7.5/1 (SP)	100		-35.1	10
-37.2	12.1		Brownish gray silt some fine quartz sand, scattered shell fragments in fine to medium gravel range. 10 YR 6/2 (ML)	100		-40.1	15
-44.6	19.5			100		-44.6	20
						Composite 0-8.0 ft.	
						Final 5/13/03	
							22.5