

DRILLING LOG		DIVISION	INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates			10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1868531.460 Y=79000.630			11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.			12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-50			13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 1 undisturbed: 0			
5. NAME OF DRILLER G Wiegman/A. Browder			14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED			15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.			16. DATE HOLE STARTED COMPLETED 12-7-02 12-7-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.			17. ELEVATION TOP OF HOLE -29.1 Ft.			
9. TOTAL DEPTH OF HOLE 19.6 Ft.			18. TOTAL CORE RECOVERY FOR BORING 98 %			
			19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-29.1	.0					-29.1
-29.8	.7		Light gray fine quartz sand, abundant shell fragments and whole shells in fine to coarse gravel range. 10 YR 7.5/0.5 (SP)			
			Light gray fine quartz sand, scattered shell fragments and whole shells in fine to coarse gravel range. 10 YR 7.5/0.5 (SP)	100	20	
-32.8	3.7		Gray silty fine quartz sand, scattered shell fragments and whole shells in fine to coarse gravel range. 10 YR 7.5/0.5 (SM)			-34.1
				100		
-38.8	9.7		Gray silt and clay, some fine quartz sand, shell fragments and whole shells. 10 YR 7/0.5-6.5/0.5 (ML)			-39.1
				100		
						-44.1
-45.5	16.4		Yellow to gray silt and clay. 10 YR 7.5/3.5-7.5/0.5 (ML)			
				100		
-47.6	18.5		Gray silty fine quartz sand. 10 YR 6.5/0.5 (SM)			
-48.7	19.6					-48.7
						Final 5/13/03