

DRILLING LOG		DIVISION	INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates			10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1872497.600 Y=76980.240			11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.			12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-51			13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER G Wiegman/A. Browder			14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED			15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.			16. DATE HOLE STARTED COMPLETED 12-7-02 12-7-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.			17. ELEVATION TOP OF HOLE -32.9 Ft.			
9. TOTAL DEPTH OF HOLE 19.7 Ft.			18. TOTAL CORE RECOVERY FOR BORING 100 %			
			19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-32.9	.0		Gray silt and clay, some fine quartz sand. 10 YR 6/0.5 (ML)			-32.9
-35.8	2.9		Yellowish-orange silt and clay. 10 YR 7/3.5 (CL)	100		
-38.1	5.2		Gray silt and clay. 10 YR 6.5/0.5 (CL)			-37.9
-39.8	6.9		Light gray to light tannish gray fine quartz sand, scattered inclusions of gray silt in collapsed burrow structures. 10 YR 8/0.5-8/1.5 (SP)	100		
				100		-42.9
						-47.9
-49.1	16.2		Brownish gray medium to fine silty sand. 10 YR 6/2 (SM)	100		
-52.6	19.7					-52.6 No samples
						Final 5/22/03