

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1877994.570 Y=80497.870				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-53				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 1 undisturbed: 0			
5. NAME OF DRILLER G Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-7-02 12-7-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -28.2 Ft.			
9. TOTAL DEPTH OF HOLE 19.6 Ft.				18. TOTAL CORE RECOVERY FOR BORING 97 %			
				19. SIGNATURE OF G. Zerillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-28.2	.0					-28.2	0
-30.2	2.0		Light tannish gray medium to fine quartz sand, abundant shell fragments and whole shells in fine to coarse gravel range. 10 YR 8/1 (SP)	100	20		2.5
-34.7	6.5		Light to medium gray fine quartz sand, scattered shell fragments in fine to medium gravel range. 10 YR 7.5/0.5-8/0.5 (SP)	100		-33.2	5
			Gray silty fine quartz sand, inclusions of gray plastic clay abundant shells fragments and whole shells in fine to coarse gravel range, few cobble sized shell fragments. 10 YR 7/0.5-7.5/0.5 (SM)	100		-38.2	10
-43.4	15.2			100		-43.2	15
-43.7	15.5		Dark gray clay. 10 YR 4.5/0.5 (CL)				
			Brown medium to fine quartz sand and silt. 10 YR 4.5/3 (SM)	100			17.5
-46.6	18.4						
-47.8	19.6		Gray silty fine quartz sand, shell fragments and whole shells. 10 YR 7/0.5-7.5/0.5 (SM)			-47.8	20
						Final 5/13/03	22.5