

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1876253.060 Y=82458.710				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-54				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 1 undisturbed: 0			
5. NAME OF DRILLER G Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-7-02 12-7-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -25.2 Ft.			
9. TOTAL DEPTH OF HOLE 18.9 Ft.				18. TOTAL CORE RECOVERY FOR BORING 84 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-25.2	0					-25.2	0
-26.7	1.5		Light tan fine quartz sand, shell fragments and whole shells in fine to coarse gravel range. 10 YR 8/1 (SP)		10		
-28.1	2.9		Brown silty fine quartz sand. 10 YR 5/3 (SM)	100			2.5
-29.5	4.3		Light brown fine quartz sand, some silt, shell fragments in fine to medium gravel range. 10 YR 7/2.5 (SP)				
-30.1	4.9		Large whole gray shells and shell fragments, matrix of fine quartz sand. 10 YR 7/0.5 (GW)			-30.2	5
			Brownish gray silty fine quartz sand, shell fragments in fine to medium gravel range. 10 YR 5/2 (SM)	100			7.5
						-35.2	10
				100			12.5
-40.6	15.4		Brown silty fine quartz sand. 10 YR 4/3.5 (SM)	100		-40.2	15
							17.5
-44.1	18.9					-44.1	20
						Final 5/13/03	22.5