

DRILLING LOG		DIVISION	INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates			10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1879488.270 Y=77974.380			11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.			12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-56			13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 1 undisturbed: 0			
5. NAME OF DRILLER G Wiegman/A. Browder			14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED			15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.			16. DATE HOLE STARTED COMPLETED 12-7-02 12-7-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.			17. ELEVATION TOP OF HOLE -29.9 Ft.			
9. TOTAL DEPTH OF HOLE 17.5 Ft.			18. TOTAL CORE RECOVERY FOR BORING 88 %			
			19. SIGNATURE OF G. Zarillo, SEA, Inc.			

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-29.9	.0					-29.9
			Light gray to tannish gray medium to fine quartz sand, abundant dark gray and tan shell fragments in fine to coarse gravel range, trace of silt and clay. 10 YR 7/0.5-7/1.5 (SP)	100	20	
-34.2	4.3					-34.9
			Brownish gray silt, some fine quartz sand. 10 YR 6.5/1 (ML)	100		
						-38.9
				100		
-43.0	13.1					-44.8
-43.3	13.4		Brown quartz sand. 10 YR 6/2.5 (SP)			
			Gray to light gray fine quartz sand. 10 YR 7/0.5-7.5/0.5 (SP)			
-45.0	15.1					-47.4
			Brown silty fine quartz sand. 10 YR 5.5/3 (SM)	100		
-47.4	17.5					
						Final 5/13/03