

DRILLING LOG		DIVISION	INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates			10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1881503.340 Y=80524.180			11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.			12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-57			13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 1 undisturbed: 0			
5. NAME OF DRILLER G Wiegman/A. Browder			14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED			15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.			16. DATE HOLE STARTED COMPLETED 12-7-02 12-7-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.			17. ELEVATION TOP OF HOLE -29.0 Ft.			
9. TOTAL DEPTH OF HOLE 19.0 Ft.			18. TOTAL CORE RECOVERY FOR BORING 93 %			
			19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-29.0	.0					-29.0
-30.8	1.9		Light gray fine quartz sand, abundant shell fragments in fine to medium gravel range. 10 YR 7.5/0.5-8/0.5 (SP)		10	
-34.1	5.1		Tannish gray fine quartz sand, trace of silt, some gray to tan shell fragments and whole shells in fine to coarse gravel range. 10 YR 7.5/-7.5/1.5 (SP)	100		
-38.8	9.8		Gray silty fine quartz sand, abundant clay, whole shells and shell fragments in fine to medium gravel range. 10 YR 6/0.5 (SM)	100		
-40.4	11.4		Gray clay and silt, shell fragments. 10 YR 5.5/0.5 (CL)			
			Gray clay and silt, scattered wood fragments. 10 YR 5.5/0.5-6/0.5 (CL)	100		
-48.0	19.0			100		
						Final 5/13/03