

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1881463.280 Y=72518.410				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-58				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER G Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-8-02 12-8-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -37.8 Ft.			
9. TOTAL DEPTH OF HOLE 19.2 Ft.				18. TOTAL CORE RECOVERY FOR BORING 97 %			
				19. SIGNATURE OFG. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-37.8	.0					-37.8	0
			Gray silty quartz sand, some clay, shell fragments and whole shells in fine to coarse gravel range. 10 YR 6.5/0.5-6.5/1 (SM)	100			2.5
-41.2	3.4		Gray silt and clay, some quartz sand. 10 YR 7/0.5-6.5/0.5 (ML)			-42.8	5
-44.6	6.8		Gray to light gray silty quartz sand. 10 YR 7.5/0.5-8/0.5 (SM)	100			7.5
-46.4	8.6		Gray silty fine quartz sand, some gray clay. 10 YR 6.5/0.5 (SM)			-47.8	10
-48.4	11.6		Gray medium to fine quartz sand. 10 YR 6/0.5 (SP)	100			12.5
-48.7	11.9		Gray silt and clay. 10 YR 6/0.5 (ML)			-52.8	15
-55.3	17.5		Gray silty quartz sand. 10 YR 6/0.5 (SM)	100			17.5
-57.0	19.2					-57.0	20
						No samples	
						final 5/22/03	
							22.5