

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1886461.830 Y=70005.170				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-59				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER G Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-8-02 12-8-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -30.2 Ft.			
9. TOTAL DEPTH OF HOLE 15.5 Ft.				18. TOTAL CORE RECOVERY FOR BORING 80 %			
18. SIGNATURE OF G. Zarillo, SEA, Inc.							

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-30.2	.0		Light tannish gray fine quartz sand, gray, tan, and white shell fragments in fine to medium gravel range. 10 YR 8/1 (SP)	100		-30.2
-34.0	3.8		Light gray medium to fine quartz sand, scattered shell fragments and whole shells in fine to coarse gravel range, trace of silt. 10 YR 7.5/0.5-8/0.5 (SP)	100		-35.2
-38.5	9.3		Gray silty sand, gray shell fragments in medium gravel range. 10 YR 7/0.5 (SM)	100		-40.2
-40.1	9.9		Gray silt and clay. 10 YR 6.5/0.5-7/0.5 (ML)	100		-45.7
-45.7	15.5					-45.7
						Composite 0-7.0 ft.
						Final 5/13/03