

DRILLING LOG		DIVISION	INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates			10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1888507.080 Y=74480.840			11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.			12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-60			13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder			14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED			15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.			16. DATE HOLE STARTED COMPLETED 12-8-02 12-8-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.			17. ELEVATION TOP OF HOLE -36.7 Ft.			
9. TOTAL DEPTH OF HOLE 19.7 Ft.			18. TOTAL CORE RECOVERY FOR BORING 100 %			
			19. SIGNATURE OF G. Zerillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-36.7	.0		Gray silt, some fine quartz sand scattered white shell fragments. 10 YR 6/0.5-6/1 (ML)	100		-36.7
-43.5	6.8		Gray clay scattered oyster shell fragments and wood chips. 10 YR 5.5/0.5 (CL)	100		-41.7
-46.8	10.1		Gray silt, large white to gray oyster shells and shell fragments in medium to coarse gravel range. 10 YR 6.5/0.5-5.5/0.5 (ML)	100		-46.7
-52.9	16.2		Gray to tannish gray silty quartz sand. 10 YR 7/0.5-6.5/1 (SM)	100		-51.7
-56.4	19.7					-56.4 No samples
						Final 5/22/03