

DRILLING LOG			DIVISION	INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates			10. SIZE AND TYPE OF BIT 4" VIBRACORE				
2. LOCATION (Coordinates or Station) X=1895470.270 Y=83482.480			11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW				
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.			12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE				
4. HOLE NO. (As shown on drawing title and file number) BC-62			13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0				
5. NAME OF DRILLER G. Wiegman/A. Browder			14. TOTAL NUMBER OF CORE BOXES 2				
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED			15. ELEVATION GROUND WATER				
7. THICKNESS OF BURDEN 0 Ft.			16. DATE HOLE STARTED COMPLETED 12-8-02 12-8-02				
8. DEPTH DRILLED INTO ROCK 0 Ft.			17. ELEVATION TOP OF HOLE -31.1 Ft.				
9. TOTAL DEPTH OF HOLE 18.6 Ft.			18. TOTAL CORE RECOVERY FOR BORING 99 %				
19. SIGNATURE OF G. Zarillo, SEA, Inc.							
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-31.1	.0					-31.1	0
-33.3	2.2		Tannish gray to brown medium to fine quartz sand, scattered whole shells and shell fragments in fine to medium gravel range, trace of silt. 10 YR 7.5/1-6/3 (SP)	100			2.5
-37.9	6.8		Brownish gray silty fine quartz sand. 10 YR 6/1-6.5/2.5 (SM)	100		-36.1	5
-40.3	9.2		Gray to brownish gray fine quartz sand, scattered dark gray shell fragments and whole shells. 10 YR 7/0.5-7/2 (SP)	100			7.5
			Light gray fine quartz sand, trace of silt in burrow structures. 10 YR 8/0.5-7.5/0.5 (SP)	100		-41.1	10
				100			12.5
				100		-46.1	15
-48.7	18.6					-48.7	17.5
						No samples	20
						Final 5/22/03	
							22.5