

DRILLING LOG		DIVISION	INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates			10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1895468.800 Y=76511.610			11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.			12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-64			13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder			14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED			15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.			16. DATE HOLE STARTED COMPLETED 12-8-02 12-8-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.			17. ELEVATION TOP OF HOLE -32.7 Ft.			
9. TOTAL DEPTH OF HOLE 18.8 Ft.			18. TOTAL CORE RECOVERY FOR BORING 98 %			
			19. SIGNATURE OF G. Zerillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-32.7	.0					-32.7
			Tannish gray fine quartz sand, silt and clay inclusions, dark gray to gray whole shells and shell fragments in fine to medium gravel range. 10 YR 7/0.5-7/1.5 (SP)	100		
-36.4	3.7					
-37.4	4.7		Gray silty quartz sand, whole shells and shell fragments. 10 YR 6.5/0.5-6/1 (SM)			-37.7
			Gray silt, some fine quartz sand, scattered large oyster shells and shell fragments in medium to coarse gravel range. 10 YR 5.5/0.5-6.5/0.5 (ML)	100		
-45.5	12.8			100		-42.7
			Orange-gray clay and silt. 10 YR 6.5/3-6.5/2 (CL)			
-47.9	15.2					-47.7
			Gray clay, scattered inclusions of wood chips. 10 YR 5/0.5-5.5/0.5 (CL)	100		
-51.5	18.8					-51.5
						No samples
						Final 5/22/03