

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1900471.290 Y=74529.390				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-65				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 1 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-8-02 12-8-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -31.3 Ft.			
9. TOTAL DEPTH OF HOLE 18.5 Ft.				18. TOTAL CORE RECOVERY FOR BORING 94 %			
				19. SIGNATURE OF G. Zerillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-31.3	.0					-31.3	0
			Light tannish gray fine quartz sand, whole shells and shell fragments in fine to medium gravel range. 10 YR 8/1 (SP)		10		
-33.4	2.1						
-34.0	2.7		Light gray fine quartz sand, abundant whole shells and shell fragments. 10 YR 8/0.5 (SW)	100			2.5
-34.8	3.5		Light tannish gray fine quartz sand, few shell fragments and whole shells in medium gravel range. 10 YR 8/1 (SP)				
			Tan to brownish gray silty fine quartz sand, shell fragments and whole shells in fine to coarse gravel range. 10 YR 6.5/2-6.5/3 (SM)	100		-36.3	5
-41.0	9.7						
-41.4	10.1		Gray silt and clay. 10 YR 6/0.5 (ML)			-41.3	10
			Yellowish-orange to gray silt. 10 YR 6.5/2-6.5/4 (ML)	100			12.5
						-46.3	15
-47.8	16.5		Gray silt. 10 YR 6.5/0.5 (ML)	100			17.5
-48.8	18.5					-48.8	18.5
							20
						Final 5/13/03	22.5