

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1902474.050 Y=79491.680				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-68				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-8-02 12-8-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -27.9 Ft.			
9. TOTAL DEPTH OF HOLE 15.3 Ft.				18. TOTAL CORE RECOVERY FOR BORING 78 %			
				19. SIGNATURE OF G. Zerillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-27.8	.0					-27.8	0
			Light tannish gray fine quartz sand, scattered shell fragments in fine to medium gravel range, worm tubes, trace of silt in burrow structures. 10 YR 8/1 (SP)	100			2.5
-32.8	5.0		Gray to light gray fine quartz sand, trace of gray silt and clay in collapsed burrow structures, trace of shell fragments in fine gravel range. 10 YR 7.5/0.5 (SP)	100		-32.8	5
-35.8	7.9		Gray silty fine quartz sand, scattered large whole shells and shell fragments in medium to coarse gravel range. 10 YR 5.5/0.5-6/0.5 (SM)			-37.8	10
-38.5	11.6		Gray clay. 10 YR 4.5/0.5 (CL)				12.5
-38.8	11.9		Gray medium to fine quartz sand, abundant clay and silt inclusions in collapsed burrows, scattered large whole shells and shell fragments in medium to coarse gravel range. 10 YR 6.5/0.5 (SP)	100		-43.2	15
-43.2	15.3						17.5
						Composite 0-6.0 ft.	20
						Final 5/13/03	22.5