

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1901465.220 Y=81423.350				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-69				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-8-02 12-8-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -27.7 Ft.			
9. TOTAL DEPTH OF HOLE 18.0 Ft.				18. TOTAL CORE RECOVERY FOR BORING 92 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-27.7	.0		Light tannish gray fine quartz sand, trace of white shell fragments in fine gravel range. 10 YR 8.5/1-8.5/1.5 (SP)			-27.7	0
-28.5	1.8		Light gray fine quartz sand, scattered gray silt and clay inclusions in collapsed burrow structures. 10 YR 7.5/0.5-8/0.5 (SM)	100			2.5
-34.5	6.8		Tan to brown fine silty quartz sand, shell fragments in fine to medium gravel range. 10 YR 6.5/1-6.5/2 (SM)	100		-32.7	5
-35.1	7.4		Tannish gray fine quartz sand, abundant silt and clay inclusions in burrow structures. 10 YR 7/0.5-7.5/1 (SM)				7.5
-35.5	7.8		Gray fine quartz sand, abundant gray to white whole shells and shell fragments in fine to coarse gravel range. 10 YR 7.5/0.5 (SP)				10
-36.0	8.3		Tannish gray fine quartz sand, abundant silt and clay inclusions in burrow structures. 10 YR 7.5/0.5 (SM)	100		-37.7	12.5
-38.0	10.3		Light gray fine quartz sand, dark gray silt and clay inclusions in collapsed burrow structures. 10 YR 8/0.5 (SM)				15
-42.1	14.4		Gray to light gray fine quartz sand, abundant shell fragments in fine to coarse gravel range. 10 YR 7/0.5-7.5/0.5 (SP)			-42.7	17.5
-42.7	15.0		Orange to orange gray silt. 10 YR 7.5/3-7.5/4 (ML)	100			20
-45.7	18.0					-45.7	22.5
Composite 0-12.0 ft.							
Final 5/13/03							