

DRILLING LOG		DIVISION	INSTALLATION	SHEET 1 OF 1
1. PROJECT Baldwin County, AL: Olsen Associates			10. SIZE AND TYPE OF BIT 4" VIBRACORE	
2. LOCATION (Coordinates or Station) X=1909471.860 Y=75993.900			11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW	
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.			12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE	
4. HOLE NO. (As shown on drawing title and file number) BC-71			13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 1 undisturbed: 0	
5. NAME OF DRILLER G. Wiegman/A. Browder			14. TOTAL NUMBER OF CORE BOXES 2	
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED			15. ELEVATION GROUND WATER	
7. THICKNESS OF BURDEN 0 Ft.			16. DATE HOLE STARTED COMPLETED 12-8-02 12-8-02	
8. DEPTH DRILLED INTO ROCK 0 Ft.			17. ELEVATION TOP OF HOLE -28.8 Ft.	
9. TOTAL DEPTH OF HOLE 18.6 Ft.			18. TOTAL CORE RECOVERY FOR BORING 92 %	
			19. SIGNATURE OF G. Zerillo, SEA, Inc.	

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-28.8	.0					-28.8	0
-28.5	.7		Light tannish gray fine quartz sand, abundant large shell fragments in medium to coarse gravel range. 10 YR 8.5/1 (SP)		10		
			Light tannish gray fine quartz sand, scattered shell fragments in fine gravel range. 10 YR 8/1-8.5/1 (SP)	100			2.5
-33.5	4.7					-33.8	5
			Tan to brownish tan fine silty quartz sand, abundant inclusions of silt and some clay in collapsed burrow structures. 10 YR 6.5/2-7.5/2 (SM)	100			7.5
						-38.8	10
				100			12.5
						-43.8	15
				100			17.5
-47.4	18.6					-47.4	
							20
						Final 5/13/03	
							22.5