

DRILLING LOG		DIVISION	INSTALLATION	SHEET 1 OF 1
1. PROJECT Baldwin County, AL: Olsen Associates		10. SIZE AND TYPE OF BIT 4" VIBRACORE		
2. LOCATION (Coordinates or Station) X=1913027.730 Y=81967.470		11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW		
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.		12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE		
4. HOLE NO. (As shown on drawing title and file number) BC-75		13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0		
5. NAME OF DRILLER G. Wiegman/A. Browder		14. TOTAL NUMBER OF CORE BOXES 2		
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED		15. ELEVATION GROUND WATER		
7. THICKNESS OF BURDEN 0 Ft.		16. DATE HOLE STARTED COMPLETED 12-11-02 12-11-02		
8. DEPTH DRILLED INTO ROCK 0 Ft.		17. ELEVATION TOP OF HOLE -29.1 Ft.		
9. TOTAL DEPTH OF HOLE 19.3 Ft.		18. TOTAL CORE RECOVERY FOR BORING 100 %		
		19. SIGNATURE OF G. Zerillo, SEA, Inc.		

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-29.1	.0					-29.1	0
			Gray to tan fine quartz sand, gray to dark gray whole shells and shell fragments in medium to coarse sand range, some silt and decayed organic matter in collapsed burrows. 10 YR 7.5/1-7.5/2 (SP)	100		Charcoal inclusion at 1.4 ft.	2.5
-32.7	3.6		Light tannish gray to very light gray fine quartz sand, trace of gray silt in collapsed burrow structure. 10 YR 8/0.5-8/1 (SP)			-34.1	5
-36.1	7.0		White to very light gray fine quartz sand, trace of silt in burrows, trace of white shell fragments in coarse sand range. 10 YR 8.5/0.5-9/0.5 (SP)	100		-38.1	7.5
-38.3	10.2		Light gray medium to fine quartz sand. 10 YR 7.5/0.5 (SP)				10
-40.2	11.1		Dark gray silt and clay, few large oyster shells. 10 YR 6/0.5 (ML)	100		-44.1	12.5
-44.5	15.4		Dark gray to orange silt and clay. 10 YR 6/1-6/2.5 (ML)	100		-48.4	15
-48.4	19.3						17.5
						Composite 0-9.0 ft.	20
						Final 5/13/03	22.5