

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1914987.750 Y=85963.080				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-78				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-11-02 12-11-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -28.2 Ft.			
9. TOTAL DEPTH OF HOLE 18.1 Ft.				18. TOTAL CORE RECOVERY FOR BORING 93 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-28.2	.0					-28.2	0
			Light gray medium to fine quartz sand, inclusions of gray silt. 10 YR 7.5/1 (SP)				
-30.0	1.8			100			2.5
			Medium to light gray quartz sand, abundant inclusions of gray plastic silt and clay, very abundant large whole shells and shell fragments. 10 YR 7/1-7.5/1 (SM)				
-31.7	3.5						
			Gray plastic silt and clay, abundant inclusions of shell fragments. 10 YR 6/0.5 (CL)			-33.2	5
				100			7.5
-36.4	8.2						
			Gray plastic clay. 10 YR 5.5/0.5 (CL)			-38.2	10
				100			12.5
-42.7	14.5						
			Gray silty sand, some gray plastic clay. 10 YR 6/0.5 (SM)			-43.2	15
				100			
-45.4	17.2						
-46.3	18.1					-46.3	17.5
			Light brownish gray medium to fine quartz sand. 10 YR 7.5/0.5 (SP)				
						No samples	20
						Final 5/22/03	
							22.5