

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1915014.810 Y=85474.860				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-79				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-11-02 12-11-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -27.5 Ft.			
9. TOTAL DEPTH OF HOLE 18.9 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-27.5	.0					-27.5	0
-28.9	1.4		Light gray medium to fine quartz sand, some large gray whole shells in coarse gravel range. 10 YR 7.5/1-8/1 (SP)				
-30.9	3.4		Medium to light gray medium to fine quartz sand, some large shell fragments and whole shells in fine to coarse gravel range. 10 YR 7/0.5-7.5/0.5 (SP)	100	10	Large whole shells at 2.4-2.5 ft.	2.5
-32.5	5.0		Very light gray medium to fine quartz sand, few scattered gray shell fragments in fine to medium gravel range. 10 YR 8/0.5 (SP)			-32.5	5
			White to very light gray medium to fine quartz sand, few scattered white shell fragments in fine gravel range. 10 YR 8.5/0.5-9/0.5 (SP)	100	8.0		7.5
				100		-37.5	10
				100		-42.5	15
				100	16.0		17.5
-46.4	18.9					-46.4	20
						Composite 0-17.0 ft.	
						Final 4/1/03	
							22.5