

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1918011.370 Y=83972.540				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-80				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-11-02 12-11-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -27.3 Ft.			
9. TOTAL DEPTH OF HOLE 18.5 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zerillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-27.3	.0					-27.3	0
-29.7	2.4		Light gray medium to fine quartz sand, scattered large shell fragments and whole shells in medium to coarse gravel range, few inclusions of silt in burrows. 10 YR 7.5/0.5 (SP)	100	10		2.5
-31.2	3.9		Gray medium to fine quartz sand, abundant inclusions of silt and organic matter in burrow structures. 10 YR 7/0.5 (SP)				
			Very light gray medium to fine quartz sand, trace of organic matter in burrow structures. 10 YR 8/0.5 (SP)			-32.3	5
				100	80		7.5
						-37.3	10
-40.4	13.1			100			12.5
			Light gray medium quartz sand, scattered gray shell fragments in medium to coarse gravel range. 10 YR 7/0.5 (SP)			-42.3	15
				100	160		17.5
-45.6	18.5					-45.6	
						Composite 0-16.0 ft.	20
						Final 4/1/03	
							22.5