

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1917973.690 Y=84991.740				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-82				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-11-02 12-11-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -28.6 Ft.			
9. TOTAL DEPTH OF HOLE 18.7 Ft.				18. TOTAL CORE RECOVERY FOR BORING 99 %			
				19. SIGNATURE OF G. Zerillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-28.6	.0					-28.6	0
-28.9	1.3		Light gray to tannish gray fine quartz sand. 10 YR 8/1-8/1.5 (SP)				
-32.2	3.6		Light to medium gray fine quartz sand, abundant large gray whole shells and shell fragments in medium to coarse gravel range, trace of silt. 10 YR 7/0.5-7.5/0.5 (SP)	100	10		2.5
			Light tannish gray to white fine quartz sand. 10 YR 8/2-9/0.5 (SP)			-33.6	5
-38.0	9.4			100	8.0		7.5
			White to very light gray medium to fine quartz sand, trace of silt in collapsed burrow structures. 10 YR 8/0.5-9/0.5 (SP)			-38.6	10
				100			12.5
						-43.6	15
				100	16.0		17.5
-47.3	18.7					-47.3	
						Composite 0-16.0 ft.	20
						Final 4/1/03	
							22.5