

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1917999.060 Y=82964.980				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-83				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 2 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-11-02 12-11-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -29.6 Ft.			
9. TOTAL DEPTH OF HOLE 20.3 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-28.6	.0					-29.6	0
-30.8	1.2		Tannish gray fine quartz sand and silt. 10 YR 7/1.5-7/2 (SM)				
			Light gray fine quartz sand, prominent burrow structures lined with gray silt and clay. 10 YR 8/0.5 (SP)	100	3.0		2.5
-34.2	4.6		White fine quartz sand, scattered inclusions of gray silt and clay in collapsed burrows, scattered white shell fragments in fine gravel range. 10 YR 8.5/0.5-9/0.5 (SP)			-34.6	5
-37.1	7.5		Very light gray fine quartz sand. 10 YR 8/0.5 (SP)	100			7.5
						-38.6	10
				100	13.0		12.5
-44.9	15.3		Gray silt, clay and some sand, large whole shells. 10 YR 5.5/0.5 (CL)			-44.6	15
-46.5	16.9		Tannish orange plastic clay and silt. 10 YR 7.5/3 (CL)	100			17.5
-49.9	20.3					-49.8	20
						Composite 0-13.0 ft.	
						Final 4/1/03	
							22.5