

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1926964.410 Y=80009.840				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-85				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-11-02 12-11-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -38.4 Ft.			
9. TOTAL DEPTH OF HOLE 18.2 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	LOG SAMPLE NUMBER	REMARKS	
-38.4	.0					-38.4	0
-38.2	.8		Light gray fine quartz sand and tannish gray silt and clay. 10 YR 8/0.5-6.5/2 (SM)				
-41.1	2.7		Light gray fine quartz sand, inclusions of gray clay and silt in burrow structures. 10 YR 8/0.5 (SP)	100			2.5
-42.0	3.6		Tannish gray silty quartz sand. 10 YR 7/1-6.5/1.5 (SM)				
			Tannish gray silt, some quartz sand. 10 YR 6/2.5 (ML)				
-44.0	5.6		Gray silt. 10 YR 5/0.5 (ML)	100		-43.4	5
-47.1	8.7		Gray clay and silt, scattered large whole oyster shells. 10 YR 4.5/0.5 (CL)	100		-46.4	10
				100		-53.4	15
-56.6	18.2					-56.6	17.5
						No samples	20
						Final 5/22/03	
							22.5