

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1927015.570 Y=84978.590				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-86				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 2 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-11-02 12-11-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -25.3 Ft.			
9. TOTAL DEPTH OF HOLE 16.9 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zerillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-25.3	.0					-25.3	0
-26.5	1.2		Light tannish gray medium to fine quartz sand. 10 YR 8/1 (SP)				
			Light gray fine quartz sand, few inclusions of gray plastic silt, scattered shell fragments in fine to medium gravel range. 10 YR 7.5/0.5 (SP)	100	10		2.5
-30.1	4.8					-30.3	5
			Medium gray to light gray fine quartz sand, mixed with inclusions of silty sand, and plastic clay. 10 YR 7.5/0.5-7/1 (SM)				
-32.3	7.0			100			7.5
			Medium gray to light gray fine quartz sand, abundant inclusions of plastic silt, abundant shell fragments in medium to coarse gravel range. 10 YR 7/1-7.5/0.5 (SP)				
-34.7	9.4					-35.3	10
			Light gray fine quartz sand, scattered shell fragments and whole shells in fine to medium gravel range. 10 YR 7.5/0.5-8/0.5 (SP)	100	12.0		12.5
-39.1	13.8					-40.3	15
			Light tannish gray fine quartz sand, few shell fragments in fine to medium gravel range. 10 YR 8/0.5-8/1.5 (SP)	100			
-41.8	16.5					-42.2	17.5
-42.2	16.9		Gray silty fine quartz sand. 10 YR 6.5/0.5-7/0.5 (SM)				
						Composite 10-4.0 ft.	20
						Final 6/24/03	22.5