

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1926007.670 Y=87961.080				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-87				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 2 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-11-02 12-11-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -20.5 Ft.			
9. TOTAL DEPTH OF HOLE 17.1 Ft.				18. TOTAL CORE RECOVERY FOR BORING 98 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-20.5	.0		Light tan fine quartz sand. 10 YR 8.5/1.5 (SP)	100		-20.5	0
-24.0	3.5		Light tanhish gray medium to fine quartz sand, scattered white to light gray shell fragments in fine to medium gravel range. 10 YR 8/0.5-8/1.0 (SP)	40		-25.5	5
-26.6	6.1		Gray to light gray medium to fine quartz sand, trace of silt scattered gray shell fragments in fine to medium gravel range. 10 YR 7/0.5-7.5/0.5 (SP)	100			7.5
-30.6	8.9		Gray plastic silt and clay. 10 YR 5.5/0.5 (CL)			-30.5	10
			Medium gray medium to fine quartz sand, trace of silt. 10 YR 7/0.5-7.5/0.5 (SP)	100	12.0		12.5
-36.6	16.1					-35.5	15
-37.6	17.1		Very light gray to white medium to fine quartz sand. 10 YR 8.5/0.5-8/0.5 (SP)	100		-37.6	17.5
						Composite 10-16.0 ft.	20
						Final 3/24/03	22.5