

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1926992.560 Y=87978.110				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-88				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-11-02 12-11-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -24.7 Ft.			
9. TOTAL DEPTH OF HOLE 19.9 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-24.7	.0					-24.7	0
			Light gray to light tannish gray fine quartz sand, scattered white shell fragments in fine to medium gravel range. 10 YR 7.5/0.5-7.5/1.5 (SP)		10		2.5
-26.8	2.2		White medium to fine quartz sand, scattered inclusions of decayed organic matter. 10 YR 9/0.5 (SP)	100			5
				100	80		7.5
						-34.7	10
-36.6	11.9		Light gray medium to fine quartz sand. 10 YR 7.5/0.5-8/0.5 (SP)	100	120		12.5
-38.4	14.7		Light gray to medium gray fine quartz sand. 10 YR 7/0.5-7.5/0.5 (SP)			-38.7	15
				100			17.5
-44.6	19.9					-44.6 Composite 0-16.0 ft.	20
						Final 6/24/03	22.5