

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1928018.320 Y=86993.190				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-89				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-11-02 12-11-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -26.2 Ft.			
9. TOTAL DEPTH OF HOLE 19.5 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
19. SIGNATURE OF G. Zerillo, SEA, Inc.							

  

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-26.2	.0					-26.2	0
-26.8	.6		Light tannish gray fine quartz sand, inclusions of decayed organic matter. 10 YR 8/0.5-7.5/1 (SP)			Clay lined burrow at 0.4-0.6 ft.	
			White medium to fine quartz sand, few scattered shell fragments in coarse gravel range. 10 YR 9/0.5 (SP)	100	1.0		2.5
						-31.2	5
				100	8.0		7.5
						-36.2	10
				100		Large shell fragment at 10.6-10.7 ft.	12.5
					15.0	-41.2	15
				100			17.5
-44.4	18.2						
-45.7	19.5		Light gray medium to fine quartz sand, inclusions of gray decayed organic matter. 10 YR 7/0.5-7/1 (SP)			-45.7	20
						Composite 0-15.0 ft.	
						Final 6/24/03	
							22.5