

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1937480.680 Y=84266.430				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-90				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-12-02 12-12-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -27.9 Ft.			
9. TOTAL DEPTH OF HOLE 17.9 Ft.				18. TOTAL CORE RECOVERY FOR BORING 99 %			
				19. SIGNATURE OF G. Zerillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-27.9	.0					-27.9	0
			Light tannish gray fine quartz sand, scattered shell fragments and whole shells in fine to medium gravel range, trace of silt and clay. 10 YR 8.5/1-8/1 (SP)	100			2.5
						-32.9	5
				100			7.5
-36.6	8.7		Light gray to tannish gray fine quartz sand, scattered silt and clay inclusions in collapsed burrows, trace of shell fragments in fine gravel range. 10 YR 8/0.5-7/1 (SP)			-37.9	10
-40.6	12.7		Tan fine quartz sand. 10 YR 7.5/1.5 (SP)	100			12.5
-41.1	13.2		Tan to brownish gray silty quartz sand. 10 YR 6.5/1 (SM)				
-42.0	14.1		Brownish gray silt, some fine quartz sand. 10 YR 6/1-6/2.5 (ML)			-42.9	15
				100			17.5
-45.8	17.9					-45.8	17.5
						Composite 0-11.0 ft.	20
						Final 5/13/03	20
							22.5