

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1939485.590 Y=84284.580				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-92				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-12-02 12-12-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -29.8 Ft.			
9. TOTAL DEPTH OF HOLE 18.0 Ft.				18. TOTAL CORE RECOVERY FOR BORING 98 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-29.8	.0		Very light gray medium to fine quartz sand, few scattered large shell fragments in medium to coarse gravel range. 10 YR 8.5/0.5 (SP)	100		-29.8	0
							2.5
							5
-36.0	6.2		Light tannish gray fine quartz sand. 10 YR 8/0.5-8/1.0 (SP)	100		-34.8	7.5
							10
-38.4	8.8		Gray silty sand. 10 YR 6/0.5 (SM)			-38.8	12.5
-38.7	9.0		Dark gray clay. 10 YR 5.5/0.5 (CL)	100			15
							17.5
-44.5	14.7		Gray silty fine quartz sand. 10 YR 6/0.5 (SM)	100		-44.8	20
							22.5
-47.8	18.0					-47.8	
						Composite 0-7.0 ft.	
						Final 5/13/03	