

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1938466.810 Y=83257.600				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-93				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 2 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-12-02 12-12-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -29.3 Ft.			
9. TOTAL DEPTH OF HOLE 18.3 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-29.3	.0					-29.3
			Light tannish gray medium to fine quartz sand, abundant gray to white whole shells and shell fragments in fine to medium gravel range. 10 YR 8.5/1 (SP)	100		
-32.1	2.8				4.0	
			Light gray fine quartz sand, scattered gray and white whole shells and shell fragments in fine to medium gravel range. 10 YR 8/0.5-8.5/0.5 (SP)			
-36.8	7.5			100	8.0	
			Very light gray to white fine quartz sand, trace of shell fragments. 10 YR 8.5/0.5-9/0.5 (SP)			
				100		
-44.7	15.4					
			Light gray fine quartz sand, trace of gray shell fragments in fine gravel range. 10 YR 8/0.5-8.5/0.5 (SP)	100		
-47.6	18.3					
						Composite 0-11.0 ft.
						Final 5/13/03