

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1939481.090 Y=83279.140				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-94				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 1 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-12-02 12-12-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -30.1 Ft.			
9. TOTAL DEPTH OF HOLE 19.6 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-30.1	0		Light tan to light white medium to fine quartz sand, scattered shell fragments and whole shells in fine to medium gravel range. 10 YR 8.5/1-9/1 (SP)	100		-30.1	0
-36.5	6.4		White to very light tan fine quartz sand, trace of shell fragments in fine gravel range. 10 YR 9/0.5-8.5/1 (SP)	100	6.0	-35.1	5
-38.5	8.4		Gray silt and clay. 10 YR 5/0.5 (CL)	100		-40.1	10
-48.4	18.3		Tan medium to fine quartz sand. 10 YR 6.5/2.5 (SP)	100		-45.1	15
-49.7	19.6					-49.7	20
						Composite 0-6.0 ft.	
						Final 5/13/03	