

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1938484.980 Y=82264.450				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-95				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-12-02 12-12-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -30.0 Ft.			
9. TOTAL DEPTH OF HOLE 18.5 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zerillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-30.0	.0					-30.0	0
-32.5	2.5		Light tannish gray fine quartz sand, scattered large whole shells in medium gravel to cobble range, scattered shell fragments in fine gravel range. 10 YR 8/1 (SP)	100			2.5
			White to very light gray fine quartz sand, scattered gray shell fragments in fine gravel range. 10 YR 8.5/0.5-9/0.5 (SP)			Shell layer at 3.1-3.3 ft.	
				100		-35.0	5
							7.5
-40.0	10.0		Light gray fine quartz sand. 10 YR 8.5/0.5 (SP)	100		-40.0	10
							12.5
-45.1	15.1		Tannish gray fine quartz sand. 10 YR 7.5/1 (SP)			-45.0	15
-45.9	15.9		White fine quartz sand. 10 YR 9/0.5 (SP)	100			
-47.6	17.6		Tannish gray fine quartz sand. 10 YR 7/1-7.5/1 (SP)				17.5
-48.5	18.5					-48.5	
						Composite 0-11.0 ft.	20
						Final 5/13/03	
							22.5