

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1939479.360 Y=82244.480				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-96				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 2 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-12-02 12-12-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -30.9 Ft.			
9. TOTAL DEPTH OF HOLE 18.3 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-30.8	.0		White fine quartz sand, trace of silt in collapsed burrows. 10 YR 9/0.5 (SP)	100	10	-30.8	0
-37.6	6.7		Very light gray fine quartz sand. 10 YR 8.5/0.5 (SP)	100	8.0	-35.9	2.5
-40.8	10.0		White fine quartz sand. 10 YR 9/0.5 (SP)	100		-40.8	5
-45.0	14.1		Light gray fine quartz sand, trace of silt. 10 YR 7.5/0.5 (SP)	100		-45.8	7.5
-45.8	15.0		White fine quartz sand. 10 YR 8.5/0.5-9/0.5 (SP)	100		-47.8	10
-47.8	17.0		Gray fine quartz sand, some brown silt, gray shell fragments in medium to coarse gravel range. 10 YR 7/0.5-7.5/0.5 (SP)	100		-48.2	12.5
-48.2	18.3						15
						Composite 0-16.0 ft.	17.5
						Final 5/13/03	20
							22.5