

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1927991.780 Y=87960.060				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-97				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 2 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-14-02 12-14-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -27.4 Ft.			
9. TOTAL DEPTH OF HOLE 17.0 Ft.				18. TOTAL CORE RECOVERY FOR BORING 90 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-27.4	.0					-27.4	0
-28.7	1.3		Light tan medium to fine quartz sand, few large gray shell fragments 10 YR 8.5/3 (SP)				
-29.2	1.8		Tan medium to fine quartz sand with large whole shells and shell fragments in fine gravel to small cobble range. 10 YR 8/3.5 (SW)	100	3.0		2.5
-30.8	3.4		White medium to fine quartz sand, few scattered inclusions of decayed organic matter. 10 YR 8.5/0.5 (SP)				
-31.8	4.4		Light gray medium to fine quartz sand, thin layers of decayed organic matter. 10 YR 8/1.5 (SP)			-32.4	5
-33.6	6.2		White medium to fine quartz sand. 10 YR 9/0.5 (SP)				
-34.6	7.2		Very light gray to tannish gray medium to fine quartz sand. 10 YR 7.5/0.5-7.5/1.5 (SP)	100	9.0		7.5
			White medium to fine quartz sand. 10 YR 9/0.5 (SP)				
-38.0	10.6					-37.4	10
-38.5	11.1		Gray medium to fine quartz sand, thin layers of gray silty sand. 10 YR 7/0.5 (SP)			Large wood fragment at 10 ft.	
			Very light gray to white medium to fine quartz sand, thin layers of gray silty sand and decayed organic matter. 10 YR 8/0.5-8.5/0.5 (SP)	100			12.5
-41.3	13.9		Dark gray plastic clay. 10 YR 5/0.5 (CL)				
-42.3	14.9		Light gray medium to fine quartz sand. 10 YR 7.5/0.5-8/0.5 (SP)			-42.4	15
-43.8	16.4		Light gray quartz sand inter-layered with gray silty sand. 10 YR 7.5/0.5-7/0.5 (SP)	100			
-44.4	17.0		Gray silty quartz sand. 10 YR 7/0.5-6.5/0.5 (SM)			-44.4	17.5
						Composite 0-13.0 ft.	20
						Final 3/24/03	
							22.5