

DRILLING LOG		DIVISION	INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates			10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1929006.610 Y=86968.990			11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.			12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-98			13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder			14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED			15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.			16. DATE HOLE STARTED COMPLETED 12-14-02 12-14-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.			17. ELEVATION TOP OF HOLE -28.8 Ft.			
9. TOTAL DEPTH OF HOLE 19.6 Ft.			18. TOTAL CORE RECOVERY FOR BORING 89 %			
19. SIGNATURE OF G. Zarillo, SEA, Inc.						

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-28.8	.0					-28.8
-31.0	2.2		Light gray to white fine quartz sand, inclusions of gray decayed organic matter. 10 YR 8.5/0.5-8.5/1.5 (SP)		1.0	
			White fine quartz sand. 10 YR 8.5/0.5-9/0.5 (SP)	100		
-36.7	7.9			100	7.0	
-37.5	8.7		Light gray fine quartz sand. 10 YR 8/0.5-8/1.5 (SP)			Thin layer of silty gray sand at 8.2 ft.
			White fine quartz sand. 10 YR 8/0.5-8.5/0.5 (SP)			
-41.4	12.6			100	13.0	
-42.2	13.4		Medium gray fine quartz sand. 10 YR 7/1 (SP)			
-42.8	14.1		Light gray to white fine quartz sand. 10 YR 8/1 (SP)			Decayed wood fragment at 14.3 ft.
-43.8	15.1		Gray to light gray fine quartz sand, trace of silt and decayed wood. 10 YR 7.5/0.5-7.5/1 (SP)			-43.8
-45.3	16.5		Gray silty sand. 10 YR 6/0.5 (SM)			
			Gray silt and clay. 10 YR 5.5/0.5 (CL)	100		
-48.4	19.6					-48.4 Composite 0-13.0 ft.
						Final 3/24/03