

DRILLING LOG	DIVISION	INSTALLATION	SHEET 1 OF 1
1. PROJECT Baldwin County, AL: Olsen Associates		10. SIZE AND TYPE OF BIT 4" VIBRACORE	
2. LOCATION (Coordinates or Station) X=1928267.730 Y=87466.660		11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW	
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.		12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE	
4. HOLE NO. (As shown on drawing title and file number) BC-101		13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0	
5. NAME OF DRILLER G. Wiegman/A. Browder		14. TOTAL NUMBER OF CORE BOXES 2	
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED		15. ELEVATION GROUND WATER	
7. THICKNESS OF BURDEN 0 Ft.		16. DATE HOLE STARTED COMPLETED 12-14-02 12-14-02	
8. DEPTH DRILLED INTO ROCK 0 Ft.		17. ELEVATION TOP OF HOLE -27.7 Ft.	
9. TOTAL DEPTH OF HOLE 18.2 Ft.		18. TOTAL CORE RECOVERY FOR BORING 100 %	
		19. SIGNATURE OF G. Zerillo, SEA, Inc.	

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-27.7	.0		White fine quartz sand, few scattered inclusions of decayed organic matter. 10 YR 9/0.5 (SP)			-27.7	0
				100	1.0		2.5
-32.8	5.1		Very light gray fine quartz sand. 10 YR 8/0.5 (SP)			-32.7	5
-35.1	7.4		Gray fine quartz sand, trace of silt. 10 YR 7/0.5-7.5/0.5 (SP)	100	8.0		7.5
-35.7	8.0		White medium to fine quartz sand. 10 YR 8.5/0.5-9/0.5 (SP)			-37.7	10
				100			12.5
-40.2	12.5		Very light gray to white fine quartz sand, few scattered inclusions of dark gray decayed organic matter. 10 YR 8.0/0.5-8.5/0.5 (SP)			Thin layer of coarse gray silty sand at 14.2-14.3 ft.	
					16.0	-42.7	15
				100			17.5
-45.9	18.2					-45.9	
						Composite 0-16.0 ft.	20
						Final 3/24/03	
							22.5