

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1927508.970 Y=88465.150				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-102				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-14-02 12-14-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -26.1 Ft.			
9. TOTAL DEPTH OF HOLE 19.0 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zerillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-26.1	.0					-26.1	0
-27.7	1.6		Tan to light gray fine quartz sand, whole shells 1/2" to 2", abundant shell fragments in fine to coarse gravel range. 10 YR 7.5/1-7.5/2 (SP)		0.5		
-29.6	3.5		White to very light gray fine quartz sand, thin layers of organic stain. 10 YR 9/0.5 (SP)	100			2.5
			White fine quartz sand. 10 YR 9.25/0.5 (SP)			-31.1	5
					6.0		
				100			7.5
-36.6	10.5		White to light gray fine quartz sand, scattered inclusions of decayed organic matter. 10 YR 8/0.5-7.5/1 (SP)			-36.1	10
					12.0		12.5
-40.6	14.5		White to very light gray fine quartz sand. 10 YR 9/0.5-8/1 (SP)			-41.1	15
-41.2	15.1		Gray to light gray fine quartz sand. 10 YR 8/1-7.5/1 (SP)	100			17.5
-45.1	19.0					-45.1	
						Composite 0-15.0 ft.	20
						Final 3/24/03	
							22.5