

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1926193.850 Y=87590.570				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-103				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-14-02 12-14-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -21.0 Ft.			
9. TOTAL DEPTH OF HOLE 18.3 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-21.0	.0		Light gray to light tannish gray medium to fine quartz sand, scattered shell fragments in medium sand to fine gravel range. 10 YR 8.5/1-8.5/2 (SP)	100	2.0	-21.0	0
-25.1	4.1		Gray to light tannish gray fine quartz sand, scattered gray to light gray shell fragments in coarse sand to fine gravel range. 10 YR 7/1-7/2 (SP)	100	8.0	Layer of large shell frag. & whole shells -26.0 at 3.7-4.0 ft.	5
-28.9	7.9		White to very light gray fine quartz sand, few inclusions of brown to gray decayed organic matter. 10 YR 8.5/0.5-9/0.5 (SP)	100	14.0	-31.0	10
-33.0	12.0		Light gray to very light gray fine quartz sand. 10 YR 8/0.5-9/0.5 (SP)	100		-36.0	15
-36.9	15.9		White fine quartz sand. 10 YR 9/0.5-9/1 (SP)	100		-39.3	17.5
-38.3	18.3					Composite 0-16.0 ft. Final 3/24/03	20
							22.5