

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1929005.780 Y=87750.240				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-107				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-14-02 12-14-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -22.0 Ft.			
9. TOTAL DEPTH OF HOLE 19.3 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-22.0	.0					-22.0	0
			Very light gray to white fine quartz sand, scattered large whole shells in coarse gravel range. 10 YR 8.5/0.5 (SP)		10		
-24.0	2.0		Very light gray to white fine quartz sand, few scattered light gray shell fragments in fine gravel range. 10 YR 8.5/0.5-9/0.5 (SP)	100			2.5
						-27.0	5
				100	8.0	Thin layer of coarse shell fragments at 7.8 ft.	7.5
-32.1	10.1		White medium to fine quartz sand, few scattered inclusions of decayed organic matter. 10 YR 8.5/0.5-9/0.5 (SP)	100		-32.0	10
						-37.0	15
-41.3	19.3			100	16.0		17.5
						-41.3	20
						Composite 0-18.0 ft.	
						Final 3/24/03	
							22.5