

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1919040.920 Y=84996.130				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-108R2				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 2 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 1			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-14-02 12-14-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -32.0 Ft.			
9. TOTAL DEPTH OF HOLE 20.3 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-32.0	.0					-32.0	0
				0			2.5
						-37.0	5
				0			7.5
						-42.0	10
				0			12.5
-44.8	12.8					-44.8	12.5
			Very light gray to light gray medium to fine quartz sand, few thin layers of crushed shell material, scattered large shell fragments in medium to coarse gravel range. 10 YR 8/0.5-8.5/0.5 (SP)	100	16.0	Large tan whole shell at 13.0-13.2 ft.	15
-49.8	17.8					-49.8	17.5
			Light tannish gray medium to fine quartz sand, scattered shell fragments in medium to coarse gravel range. 10 YR 8.5/1-8.5/1.5 (SP)	100	20.0	Final 4/1/03	20
-52.3	20.3					-52.3	20
							22.5