

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1848973.920 Y=71025.100				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-109				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-15-02 12-15-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -24.2 Ft.			
9. TOTAL DEPTH OF HOLE 18.5 Ft.				18. TOTAL CORE RECOVERY FOR BORING 98 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-24.2	.0					-24.2	0
-25.0	.8		Light tan fine quartz sand, abundant gray to light gray shell fragments in fine to medium gravel range. 10 YR 8/1.5 (SP)				
			Light tan fine quartz sand, scattered gray, tan, and white shell fragments in fine to medium gravel range, occasional large shell fragments in coarse gravel range. 10 YR 8/1.5 (SP)	100			2.5
-29.7	5.5					-29.2	5
-30.4	6.2		Light gray fine quartz sand, very abundant gray, tan, and white shell fragments in fine to coarse gravel range. 10 YR 7/0.5-7.5/0.5 (SW)				
			Light gray fine quartz sand, scattered white to gray shell fragments in fine to medium gravel range. 10 YR 7.5/0.5 (SP)	100			7.5
						-34.2	10
				100			12.5
						-38.2	15
				100		Thin clay layer at 16.2 ft.	
-42.7	18.5					-42.7	17.5
						Composite 0-18.0 ft.	20
						Final 5/1/03	
							22.5