

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1849972.740 Y=68990.690				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-110				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-15-02 12-15-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -26.0 Ft.			
9. TOTAL DEPTH OF HOLE 18.3 Ft.				18. TOTAL CORE RECOVERY FOR BORING 92 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-26.0	.0		Light tan medium to fine quartz sand, scattered dark gray to light tan shell fragments in fine to coarse gravel range. 10 YR 8.5/2-8/2.5 (SP)	100		-26.0	0
-30.2	4.2		Light to medium gray fine quartz sand, few scattered shell fragments in fine to medium gravel range. 10 YR 7.5/0.5-7/1 (SP)	100		-31.0	5
-37.8	11.8		Tannish gray fine quartz sand and brown silt in large burrow structure. 10 YR 7.5/2-7.5/2.5 (SM)	100		-36.0	10
-38.3	12.3		Light gray fine quartz sand. 10 YR 7.5/1 (SP)	100		-41.0	15
-41.1	15.1		Brownish gray fine quartz sand, some silt and clay in numerous collapsed burrow structures. 10 YR 7/1-7/2 (SP)	100		-44.3	17.5
-43.7	17.7		Dark gray silty quartz sand. 10 YR 8/0.5 (SM)				20
-44.3	18.3					No samples	
						Final 5/22/03	
							22.5