

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1852490.130 Y=70505.350				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-111				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 1 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-15-02 12-15-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -32.2 Ft.			
9. TOTAL DEPTH OF HOLE 12.1 Ft.				18. TOTAL CORE RECOVERY FOR BORING 81 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-32.2	.0					-32.2	0
-33.1	.9		Light tan fine quartz sand. 10 YR 7.5/2.5 (SP)				
			Tannish light gray fine quartz sand, trace of silt and clay in burrow structures, scattered whole shells and shell fragments in fine to coarse gravel range. 10 YR 7.5/1-7.5/1.5 (SP)	100	3.0		2.5
-36.4	4.2		Tan fine quartz sand, some silt. 10 YR 6.5/2 (SM)			-37.2	5
				100			7.5
-40.8	8.6		Tan to brown silty sand. 10 YR 6/1.5-6/2.5 (SM)			-42.2	10
				100			
-44.3	12.1					-44.3	12.5
							15
							17.5
							20
							22.5
						No composite	
						Final 5/1/03	