

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1855503.420 Y=71512.130				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-112				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-15-02 12-15-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -29.3 Ft.			
9. TOTAL DEPTH OF HOLE 19.0 Ft.				18. TOTAL CORE RECOVERY FOR BORING 98 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-28.3	.0					-28.3	0
-30.5	1.2		Light gray medium to fine quartz sand, abundant large whole shells and shell fragments in fine to coarse gravel range. 10 YR 8.0/0.5-7.5/0.5 (SP)				
			Light gray fine quartz sand, scattered large whole shells and few shell fragments in fine to medium gravel range, trace of silt and clay in burrow structures. 10 YR 7.5/0.5-8/0.5 (SP)	100			2.5
						-34.3	5
				100			7.5
-38.5	9.2		Gray silty fine quartz sand. 10 YR 6/0.5 (SM)			-38.3	10
				100			12.5
-42.4	13.1		Gray silt and clay. 10 YR 6/0.5 (ML)			-44.3	15
-45.0	15.7		Light gray silt. 10 YR 7.5/0.5-8/0.5 (ML)				
-46.4	17.1		Gray to orange silt and clay. 10 YR 6/0.5-7/3.5 (ML)	100			17.5
-48.3	19.0					-48.3	
						Composite 0-8.0 ft.	20
						Final 5/13/03	
							22.5