

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1854015.670 Y=73018.660				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-113R1				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-15-02 12-15-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -27.4 Ft.			
9. TOTAL DEPTH OF HOLE 13.6 Ft.				18. TOTAL CORE RECOVERY FOR BORING 70 %			
18. SIGNATURE OF G. Zarillo, SEA, Inc.							

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-27.4	.0					-27.4
-29.3	1.9		Light gray fine quartz sand, scattered large whole shells and shell fragments in medium to coarse gravel range. 10 YR 8/0.5 (SP)		1.0	
-29.6	2.2		Gray to tan large whole shells and shell fragments mixed with fine quartz sand. 10 YR 7.5/0.5 (SW)	100		
			Light gray fine quartz sand, few scattered shell fragments and whole shells in fine to medium gravel range. 10 YR 7/0.5-7.5/0.5 (SP)		6.0	Large whole olive shell at 5.9 ft.
-35.5	8.1			100		
-36.5	9.1		Tannish gray fine quartz sand, trace of silt. 10 YR 6.5/1-6.5/1.5 (SP)			
			Light gray fine quartz sand, trace of shell fragments in fine to medium gravel range. 10 YR 7/0.5-7.5/0.5 (SP)		11.0	
-40.5	13.1			100		
-41.0	13.6		Tannish gray silty quartz sand. 10 YR 6.5/2 (SM)			
						Composite 0-11.0 ft.
						113R1 & 113R2 Composite combined.
						Final 4/15/03