

DRILLING LOG		DIVISION	INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates			10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1854018.900 Y=76001.940			11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.			12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-114			13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder			14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED			15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.			16. DATE HOLE STARTED COMPLETED 12-15-02 12-15-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.			17. ELEVATION TOP OF HOLE -25.6 Ft.			
8. TOTAL DEPTH OF HOLE 19.9 Ft.			18. TOTAL CORE RECOVERY FOR BORING 100 %			
			19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-25.6	.0					-25.6
-26.4	.8		Light gray fine quartz sand, abundant gray to light gray shell fragments in fine to medium gravel range. 10 YR 8/0.5 (SP)		10	
			Light gray fine quartz sand, few scattered shell fragments in fine to coarse gravel range, scattered silt and clay inclusions in burrow structures. 10 YR 7.5/0.5-8/0.5 (SP)	100		
					40	-30.6
				100		
					120	-35.6
-38.6	13.0		Light gray fine quartz sand, abundant silt and clay inclusions in burrow structures. 10 YR 7.5/0.5-7/0.5 (SP)	100		
-39.8	14.2		Gray silty sand, large gray to white shell fragments. 10 YR 6/0.5 (SM)			
				100		
						-40.6
-45.5	19.9					-45.5 Composite 0-12.0 ft.
						Final 4/15/03