

DRILLING LOG			DIVISION	INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates			10. SIZE AND TYPE OF BIT 4" VIBRACORE				
2. LOCATION (Coordinates or Station) X=1855034.090 Y=77475.340			11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW				
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.			12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE				
4. HOLE NO. (As shown on drawing title and file number) BC-115			13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0				
5. NAME OF DRILLER G. Wiegman/A. Browder			14. TOTAL NUMBER OF CORE BOXES 2				
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED			15. ELEVATION GROUND WATER				
7. THICKNESS OF BURDEN 0 Ft.			16. DATE HOLE STARTED COMPLETED 12-15-02 12-15-02				
8. DEPTH DRILLED INTO ROCK 0 Ft.			17. ELEVATION TOP OF HOLE -25.5 Ft.				
9. TOTAL DEPTH OF HOLE 20.1 Ft.			18. TOTAL CORE RECOVERY FOR BORING 100 %				
			19. SIGNATURE OF G. Zarillo, SEA, Inc.				
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-25.5	.0					-25.5	0
-26.0	.5		Light gray fine quartz sand, abundant large shells and shell fragments in fine to coarse gravel range. 10 YR 7.5/0.5 (SP)				
			Light gray fine quartz sand, scattered gray shell fragments in fine to medium gravel range, few inclusions of silt and clay in collapsed burrow structures. 10 YR 7.5/0.5 (SP)	100			2.5
						-30.5	5
				100			7.5
-35.9	10.4		Gray silty quartz sand, scattered gray to white shell fragments in medium to coarse gravel range. 10 YR 6/0.5 (SM)	100		-35.5	10
							12.5
						-40.5	15
				100			17.5
-45.6	20.1					Composite 0-8.0 ft.	20
						Final 4/15/03	
							22.5