

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1855975.590 Y=74619.410				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-116				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-15-02 12-15-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -26.1 Ft.			
9. TOTAL DEPTH OF HOLE 19.4 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zerillo, SEA, Inc.			

  

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-26.1	.0					-26.1	0
-26.8	.7		Light tannish gray medium to fine quartz sand, few scattered dark gray shell fragments in fine gravel range. 10 YR 8/1 (SP)		10		
-28.1	2.0		Light gray fine quartz sand, abundant gray to dark gray whole shells and shell fragments in fine to coarse gravel range. 10 YR 7.5/0.5-8/0.5 (SP)	100			2.5
			Light gray fine quartz sand, few scattered gray to dark gray shell fragments in fine to medium gravel range, few silt and clay inclusions in collapsed burrow structures. 10 YR 7.5/0.5-8/0.5 (SP)		40	-31.1	5
				100			7.5
					110	-36.1	10
				100			12.5
-38.5	13.4		Gray silty quartz sand, scattered large whole shells. 10 YR 6/0.5 (SM)			-41.1	15
				100			17.5
-45.5	19.4					-45.5	20
						Composite 0-11.0 ft.	
						Final 4/15/03	