

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1864047.630 Y=67996.200				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-117				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-15-02 12-15-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -34.5 Ft.			
9. TOTAL DEPTH OF HOLE 19.4 Ft.				18. TOTAL CORE RECOVERY FOR BORING 99 %			
				19. SIGNATURE OF G. Zerillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-34.5	.0					-34.5	0
			Light gray fine quartz sand, scattered silt and clay inclusions in collapsed burrow structures, trace of shell fragments in fine to medium gravel range. 10 YR 7.5/0.5-8/0.5 (SP)	100			2.5
-37.5	3.0		Gray silty sand. 10 YR 6.5/0.5 (SM)			-38.5	5
-41.0	6.5		Gray silty sand, scattered large whole shells and shell fragments. 10 YR 6/0.5 (SM)	100		-44.5	10
				100			12.5
-49.8	15.3		Light tannish gray fine quartz sand, silt and clay inclusions. 10 YR 8/1 (SM)	100		-49.5	15
-53.4	18.9						17.5
-53.9	19.4		Light gray to light tan fine quartz sand, clay inclusions. 10 YR 8.5/1 (SP)			-53.9	20
						No samples	
						Final 5/22/03	
							22.5