

DRILLING LOG		DIVISION		INSTALLATION	
1. PROJECT Baldwin County, AL: Olsen Associates		10. SIZE AND TYPE OF BIT 4" VIBRACORE		SHEET 1 OF 1	
2. LOCATION (Coordinates or Station) X=1859541.930 Y=77993.100		11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.		12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-118		13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder		14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED		15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.		16. DATE HOLE STARTED COMPLETED 12-15-02 12-15-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.		17. ELEVATION TOP OF HOLE -25.4 Ft.			
9. TOTAL DEPTH OF HOLE 19.9 Ft.		18. TOTAL CORE RECOVERY FOR BORING 99 %			
		19. SIGNATURE OF G. Zarillo, SEA, Inc.			

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-25.4	.0					-25.4
-26.1	.7		Light gray medium to fine quartz sand, abundant gray to white shell fragments and whole shells in fine to coarse gravel range. 10 YR 8/0.5-8.5/0.5 (SP)			
			Light gray fine quartz sand, scattered shell fragments and whole shells in fine to coarse gravel range. 10 YR 8/0.5 (SP)	100		
						-30.4
				100		
						-35.4
				100		
-38.0	13.6		Gray sand and silt. 10 YR 7/0.5 (SM)			
-38.8	14.5		Gray silty sand, scattered large shell fragments and whole shells. 10 YR 6.5/0.5 (SM)			-40.4
				100		
-44.6	19.2		Gray silt. 10 YR 6/0.5 (ML)			
-45.3	19.9					-45.3 Composite 0-8.0 ft.
						Final 5/13/03